

ZO10-ZO13 MAZDA 3 AND MAZDASPEED 3 TOE TAG LICENSE PLATE RELOCTION KIT

Tools Required:

Socket wrench Torque wrench 10mm, 14mm & 22mm deep socket 10mm wrench Loctite (optional)

1. With your hand, carefully remove the tow hook cover from the front bumper.



- 2. Using a 22mm socket install the aluminum hex bolt in to the bumper. Then, using a torque wrench, tighten to 45ft/lbs or 540 in/lbs.
 - ➤ If it's difficult to thread the aluminum hex bolt in to the bumper, stop. Use the OEM tow hook and some WD40 or PB Blaster to clean the threads.



- 3. Place the external tooth lock washer on to the 14mm bolt provided with your kit, add a couple of drops of Loctite to the threads and attach the Toe Tag mounting bracket to the aluminum hex bolt.
 - ➤ If you're parked on a level surface you may use a level across the top two ears of the bracket.
- 4. Tighten and torque the bolt using a 14mm socket and torque wrench to 145in/lbs or 13ft/lbs.
 - ➤ Do not exceed 145in/lbs or 13ft/lbs or the hex bolt will be damaged.



5. Using a 10mm socket and 10mm socket wrench, attach your license plate to the Toe Tag using the 4-10mm bolts, 8-flat washers and 4-10mm nyloc nuts.



Congratulations!! You've just completed the installation of your JBR Toe Tag License Plate Relocation Kit!!

SHIPPING

All orders are carefully inspected and packaged prior to shipment. The recipient must inspect all shipments for damage and report any damage to the carrier and JAMES BARONE RACING immediately. JAMES BARONE RACING is not responsible for damage that occurs during shipping.

RETURNS:

All sales are final. JAMES BARONE RACING will only except returns in the event of a manufacturer's defect. Defective items will be exchanged for the identical item or repaired at our discretion. Return shipping costs are the responsibility of the purchaser. An RMA # (Return to Manufacturer Authorization Number) Must accompany all returns. In rare cases where a return is accepted a 15% restocking fee will be deducted from the refund or credit. Shipping charges are non- refundable. No returns or exchanges will be accepted after 30 days.

DISCLAIMERS:

Failure to carefully follow the installation instructions for your JAMES BARONE RACING product could result in significant property damage, personal injury, injury to others or even death. Please take the time to read and thoroughly understand the instructions prior to installation. The instructions are as accurate as possible and may vary slightly from model year to model year. Professional installation is recommended. Neither JAMES BARONE RACING nor any of its employees, officers, directors, or shareholders will accept responsibility for improper use or installation of our products. JAME BARONE RACING is not responsible for the misuse, incorrect installation, or failure of any product we sell. Under no circumstances, including but not limited to negligence, will JAMES BARONE RACING be liable for special or consequential damages that result from the use or inability to use our products. JAMES BARONE RACING does not assume responsibility for any damage to the user, driver, passenger or vehicle resulting from the operation of a JAMES BARONE RACING product. PLEASE DRIVE RESPONSIBLY.

WARRANTY:

All JAMES BARONE RACING products carry a lifetime warranty to the original purchaser. Warranty is non-transferable. Warranty does not cover damage or failure caused by abuse, misuse, faulty installation or repairs not conducted by JAMES BARONE RACING. JAMES BARONE RACING is not liable for consequential damages arising from the use of our products or any indirect damages resulting in the loss of property, revenue or costs for towing, removal, installation, or re-installation. To receive warranty service you must contact JAMES BARONE RACING to receive an RMA # (Return to Manufacturer Authorization Number) at which time you will be provided with instructions for returning the faulty product

CONTACT:

If you have questions or problems, e-mail us at jamesbaroneracing@gmail.com. Posting questions or problems in the forums or other social media outlets will only delay you from getting the correct answer or personalized attention from us.